

## Pharmacy Refrigerators HYC-940



### Five Alarm Functions

High/low temperature, power failure, sensor error, low battery, door ajar



### Air Cooling, Auto Defrost

Better cabinet temperature uniformity, auto defrost



### Adjustable Shelves

The shelves are adjustable to any height to fulfill different requirements



### Heated Double Pane Glass Door

Clear display of stored products without condensation at 32 °C and 85% relative humidity condition



### Self Closing Door

Energy conserving, maintains temperature uniformity to protect valuable samples

## Ergonomic Design



High Accuracy  
Temperature Control



Interior  
LED



Lockable  
Design

# Specifications

## HYC-940

### Technical Data

|               |                            |
|---------------|----------------------------|
| Cabinet Type  | Upright, double glass door |
| Climate Class | N                          |
| Cooling Type  | Forced air cooling         |
| Defrost Mode  | Auto                       |
| Refrigerant   | CFC-Free                   |
| Noise((dB(A)) | 45                         |

### Performance

|               |     |
|---------------|-----|
| Temp Range( ) | 2~8 |
|---------------|-----|

### Control

|            |                |
|------------|----------------|
| Controller | Microprocessor |
| Display    | LED            |

### Electrical Data

|                       |            |            |        |
|-----------------------|------------|------------|--------|
| Power Supply(V/Hz)    | 220-240/50 | 208~230/60 | 115/60 |
| Power(W)              | 850        | 770        | 850    |
| Electrical Current(A) | 4.5        | 4.5        | 11     |

### Dimensions

|                            |                                      |
|----------------------------|--------------------------------------|
| Capacity(L/Cu.Ft)          | 890/31.4                             |
| Net/Gross Weight(approx)   | 227/279(kg) 500.4/615.1(lbs)         |
| Interior Dimensions(W*D*H) | 1030*590*1425(mm) 40.6*23.2*56.1(in) |
| Exterior Dimensions(W*D*H) | 1130*755*1980(mm) 44.5*29.7*78.0(in) |
| Packing Dimensions(W*D*H)  | 1250*850*2130(mm) 49.2*33.5*83.9(in) |



### Functions

|               |   |
|---------------|---|
| High/Low Temp | Y |
| Remote System | Y |
| Power Failure | Y |
| Sensor Error  | Y |
| Low Battery   | Y |
| Door Ajar     | Y |

### Accessories

|                 |          |
|-----------------|----------|
| Caster          | Y        |
| Foot            | Y        |
| Test Hole       | Y        |
| Shelves /Basket | 12/-     |
| USB Interface   | Optional |

### Others

|             |    |
|-------------|----|
| Certificate | CE |
|-------------|----|

haiermedical.co.nz  
 0800 222 812  
 Represented in Aotearoa nz by:  
 CCAT Scientific  
 info@ccat.co.nz



Note: If slight difference occurs between pictures and actual products, please refer to actual products. Our company reserves the right of final interpretation to this brochure and please contact with us for further information you might need.



Scan 2D barcode with your mobile device to learn more information about Haier Biomedical